

QT-Brightek Chip LED Series

SMD 1205 Bi-Color LED

Part No.: QBLP655-OIW

O: Orange
IW: White

Product: QBLP655-OIW	Date: August 02, 2018	Page 1 of 12
	Version# 1.1	

Table of Contents:

Introduction	3
Electrical / Optical Characteristic (Ta=25 °C)	4
Absolute Maximum Rating	4
Chromaticity Coordinates for White	6
Characteristic Curves.....	7
Solder Profile & Footprint	9
Packing	10
Labeling	11
Ordering Information	11
Revision History	12
Disclaimer	12

Introduction

Feature:

- Diffused lens
- Package in tape and reel
- Ultra bright 1205 package
- InGaN technology for IW
- AlInGaP technology for O
- Viewing angle: 140 degrees
- Reverse Mountable

Description:

These ultra-bright 655R LEDs have a height profile of 1.10mm. With a combination of high brightness output and small footprint, these LEDs are ideal for keypad backlighting and status indication.

Application:


- Status indication
- Back lighting application

Certification & Compliance:

- TS16949
- ISO9001
- RoHS Compliant



Dimension:



Units: mm / tolerance = +/-0.1mm

Electrical / Optical Characteristic (Ta=25 °C)

Product	Color	I _F (mA)	V _F (V)		λ _D (nm)			I _V (mcd)	
			Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.
QBLP655-OIW	Orange	20	2.0	2.5	600	605	610	40	66
	White	20	3.1	3.7	-	X=0.29 Y=0.28	-	160	320

Absolute Maximum Rating

Material	P _d (mW)	I _F (mA)	I _{FP} (mA)*	V _R (V)	T _{OP} (°C)	T _{ST} (°C)	T _{SOL} (°C)**
AllnGaP (R/AG/Y/O)	75	30	125	5	-40 ~ +85	-40 ~ +100	260
InGaN (IB/IG/IW)	120	30	125	5	-40 ~ +85	-40 ~ +100	260

*Duty 1/8 @ 1kHz

**IR Reflow for no more than 10 sec @ 260 °C

Forward Voltage V_F for AllnGaP @ I_F=20mA

Bin	Min.	Max.	Unit
□	1.7	2.5	V

Forward Voltage V_F for InGaN @ I_F=20mA

Bin	Min.	Max.	Unit
f	2.8	3.1	V
g	3.1	3.4	
h	3.4	3.7	

Luminous Intensity I_V @ $I_F=20mA$

Bin	Min.	Max.	Unit
F	40	50	mcd
G	50	63	
H	63	80	
I	80	100	
J	100	125	
K	125	160	
L	160	200	
M	200	250	
N	250	320	
O	320	400	
P	400	500	


Dominant Wavelength λ_D for Orange @ $I_F=20mA$

Bin	Min.	Max.	Unit
p	600	605	nm
q	605	610	

Note:

Tolerance of measurement of forward voltage: $\pm 0.1V$ Tolerance of measurement of luminous intensity: $\pm 15\%$ Tolerance of measurement of dominant wavelength: $\pm 2nm$

Chromaticity Coordinates for White









Rank	Chromaticity coordinates				
C1	X	0.2500	0.2700	0.2700	0.2500
	Y	0.2500	0.2775	0.2325	0.2050
C2	X	0.2700	0.2900	0.2900	0.2700
	Y	0.2775	0.3050	0.2600	0.2325
D1	X	0.2900	0.3100	0.3100	0.2900
	Y	0.3050	0.3325	0.2875	0.2600
D2	X	0.3100	0.3300	0.3300	0.3100
	Y	0.3325	0.3600	0.3150	0.2875







Note:
Tolerance of measurement of color coordinates: ± 0.01

Characteristic Curves

AllnGaP (O)




InGaN (IW)




Solder Profile & Footprint

-The recommended reflow soldering profile is as follows (temperatures indicated are as measured on the surface of the LED resin):



Recommended Pad Layout




Units: mm

tolerance: +/- 0.1mm


Packing

Reel Dimension:




Unit: mm

Tape Dimension:




Unit: mm

Arrangement of Tape:



Packaging Specifications:



Labeling

Part No: _____

Customer P/N: _____

Item: _____

Q'ty: _____

Vf: _____

Iv: _____

WI: _____

Date: _____

Made in China**Ordering Information**

Part #	Orderable Part #	Spec Range	Quantity per reel
QBLP655-OIW	QBLP655-OIW	Iv=66mcd typ. @ 20mA / $\lambda_D=600-610\text{nm}$	3,000 units
		Iv=320mcd typ. @ 20mA / CCT Coordinate: (X=0.29, Y=0.28) typ.	

Revision History

Description:	Revision #	Revision Date
New Release of QBLP655-OIW	V1.0	07/26/2017
Amend the white brightness	V1.1	08/02/2018

Disclaimer

QT-BRIGHTTEK reserves the right to make changes without further notice to any products herein to improve reliability, function or design. QT-BRIGHTTEK does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

Life Support Policy

QT-BRIGHTTEK's products are not authorized for use as critical components in life support devices or systems without the express written approval of QT-BRIGHTTEK. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Product: QBLP655-OIW	Date: August 02, 2018	Page 12 of 12
	Version# 1.1	