


**Feature:**

- High Isolation voltage between input and output (Viso = 5000V rms)
- Zero voltage crossing
- Operating Temperature up to 100 °C
- Available in Tube or Tape and reel
- Available with standard DIP-6, Wide lead bend, and SMD lead bend options.
- Conventional black housing package



**Schematic:**Pin Configuration


1. Anode
2. Cathode
3. No Connection
4. Terminal
5. Substrate  
(do not connect)
6. Terminal

**Certification & Compliance:**

- Pb free and RoHS Compliant
- UL recognized (File # E338132)
- VDE recognized (File # 40030457)



**Dimension:****6-Pin Dip (standard):****Wide lead bend (Option W):**

**SMD lead bend (Option S):**

All Dimensions are in mm

Tolerance = +/- 0.1mm

**Absolute Maximum Rating**

| Symbol           | Parameter                             | Rating         | Units |   |
|------------------|---------------------------------------|----------------|-------|---|
| T <sub>STG</sub> | Storage Temperature                   | -55 ~ 150      | °C    |   |
| T <sub>OPR</sub> | Operating Temperature                 | -55 ~ 100      | °C    |   |
| T <sub>SOL</sub> | Lead Solder Temperature               | 260 for 10 sec | °C    |   |
| P <sub>TOT</sub> | Total Power Dissipation               | 250            | mW    |   |
| <b>EMITTER</b>   |                                       |                |       |   |
| I <sub>F</sub>   | Continuous Forward Current            | 60             | mA    |   |
| V <sub>R</sub>   | Reverse Voltage                       | 6              | V     |   |
| P <sub>D</sub>   | Power Dissipation                     | 100            | mW    |   |
|                  | Power Dissipation Derated above 25°C  | 1.41           | mW/°C |   |
| <b>DETECTOR</b>  |                                       |                |       |   |
| P <sub>D</sub>   | Power Dissipation                     | 150            | mW    |   |
|                  | Power Dissipation Derated above 25 °C | 1.76           | mW/°C |   |
| V <sub>DRM</sub> | Off-state Output Terminal Voltage     | Q303X series   | 250   | V |
|                  |                                       | Q304X series   | 400   |   |
|                  |                                       | Q306X series   | 600   |   |
|                  |                                       | Q308X series   | 800   |   |
| I <sub>TSM</sub> | Peak Repetitive Surge Current         | 1              | A     |   |

**Electrical Characteristic** ( $T_A=25\text{ }^\circ\text{C}$ )

**Emitter**

| Symbol | Characteristic  | Test Condition      | Range |     |     | Unit          |
|--------|-----------------|---------------------|-------|-----|-----|---------------|
|        |                 |                     | Min   | Typ | Max |               |
| $V_F$  | Forward Voltage | $I_F = 30\text{mA}$ | -     | -   | 1.5 | V             |
| $I_R$  | Reverse Current | $V_R = 6\text{V}$   | -     | -   | 10  | $\mu\text{A}$ |


**Detector**

| Symbol             | Characteristic                          | Device                           | Test Condition  | Range |     |     | Unit             |
|--------------------|---|----------------------------------|---|-------|-----|-----|------------------|
|                    |   |                                  |   | Min   | Typ | Max |                  |
| $I_{\text{DRM-1}}$ | Peak Blocking Current                   | Q303X<br>/Q304X series           | $V_{\text{DRM}} = \text{Rated } V_{\text{DRM}},$<br>$I_F = 0\text{mA}$                                | -     | -   | 100 | nA               |
|                    |   | Q306X<br>/Q308X series           |   | -     | -   | 500 |                  |
| $I_{\text{DRM-2}}$ | Leakage in inhibited state              |                                  | $I_F = \text{Rated } I_{\text{FT}},$<br>$V_{\text{DRM}} = \text{Rated } V_{\text{DRM}},$<br>off state | -     | -   | 500 | $\mu\text{A}$    |
| $V_{\text{TM}}$    | Peak on-state voltage                   |                                  | $I_{\text{TM}} = 100\text{mA peak},$<br>$I_F = \text{Rated } I_{\text{FT}}$                           | -     | -   | 3.0 | V                |
| dv/dt              | Critical Rate of Rise off-state voltage | Q303X<br>/Q304X<br>/Q306X series | $V_{\text{PEAK}} = \text{Rated } V_{\text{DRM}},$<br>$I_F = 0$<br>(refer to test circuit for dv/dt)   | 1000  | -   | -   | V/ $\mu\text{s}$ |
|                    |   | Q308X series                     |   | 600   | -   | -   |                  |
| $V_{\text{INH}}$   | Inhibit voltage                         |                                  | $I_F = \text{rated } I_{\text{FT}},$<br>MT1-MT2 voltage above which device will not trigger off-state | -     | -   | 20  | V                |


**Transfer Characteristic:**

| Symbol           | Characteristic      | Device         | Test Condition                | Range           |     |     | Unit |
|------------------|---------------------|----------------|-------------------------------|-----------------|-----|-----|------|
|                  |                     |                |                               | Min             | Typ | Max |      |
| I <sub>FT</sub>  | LED Trigger Current | Q3031          | Main terminal<br>voltage = 3V | -               | -   | 15  | mA   |
|                  |                     | Q3041          |                               | -               | -   |     |      |
|                  |                     | Q3061          |                               | -               | -   |     |      |
|                  |                     | Q3081          |                               | -               | -   |     |      |
|                  |                     | Q3032          |                               | -               | -   | 10  |      |
|                  |                     | Q3042          |                               | -               | -   |     |      |
|                  |                     | Q3062          |                               | -               | -   |     |      |
|                  |                     | Q3082          |                               | -               | -   |     |      |
|                  |                     | Q3033          |                               | -               | -   | 5   |      |
|                  |                     | Q3043          |                               |                 |     |     |      |
|                  |                     | Q3063          |                               |                 |     |     |      |
|                  |                     | Q3083          |                               |                 |     |     |      |
|                  |                     | I <sub>H</sub> |                               | Holding Current |     |     |      |
| V <sub>ISO</sub> | Isolation voltage   |                |                               | 5000            | -   | -   | V    |


**Characteristic Curves:**




**Figure 7. Off-State Output Terminal Voltage vs. Ambient Temperature**



**Figure 8. Leakage in Inhibit State vs. Ambient Temperature**





**Figure 9. Inhibit Voltage vs. Ambient Temperature**







**Test Circuit for static dv/dt:**



The high voltage pulse is set to the required  $V_{PEAK}$  value and applied to the D.U.T. output side through the RC circuit above. LED current is not applied. The waveform  $V_T$  is monitored using a x100 scope probe. By varying  $R_{TEST}$ , the  $dv/dt$  (slope) is increased, until the D.U.T. is observed to trigger (waveform collapses). The  $dv/dt$  is then decreased until the D.U.T. stops triggering. At this point,  $\tau_{RC}$  is recorded and the  $dv/dt$  calculated.

$$dv/dt = \frac{0.632 \times V_{PEAK}}{\tau_{RC}}$$

**Solder Profile & Footprint:**




Recommended Solder Footprint for SMD Leadform

Units: mm


tolerance: +/- 0.1mm

**Packing & Labeling:  
Tape Dimension:**



| Dimension No.  | A        | B        | Do         | D1         | E        | F       |
|----------------|----------|----------|------------|------------|----------|---------|
| Dimension (mm) | 10.4±0.1 | 7.52±0.1 | 1.5+0.1/-0 | 1.5+0.1/-0 | 1.75±0.1 | 7.5±0.1 |

| Dimension No.  | Po       | P1      | P2      | t         | W        | K       |
|----------------|----------|---------|---------|-----------|----------|---------|
| Dimension (mm) | 4.0±0.15 | 1.6±0.1 | 2.0±0.1 | 0.35±0.03 | 16.0±0.2 | 4.5±0.1 |

**Device Marking:**

Q = QT-Brightek Corporation  
QXXX = Device Part Number  
F = Country of Origin  
R = Binning Option  
Y = Year  
WW = Week  
V = VDE Option

|  |                        |               |
|--|------------------------|---------------|
| Product: Q303X/ Q304X/ Q306X/ Q308X series | Date: February 1, 2011 | Page 12 of 15 |
|  | Version# 1.1           |               |

### Ordering Information:

| Part Number  | Orderable Part Number             | Options | Description   | Quantity per packing |
|--------------|-----------------------------------|---------|---|----------------------|
| Q303X series | Q3031 / Q3032 / Q3033             | None    | Standard 6pin DIP                                     | 60pcs / Tube         |
|              | Q3031V / Q3032V / Q3033V          | None    | Standard 6 pin Dip + With VDE marking                 | 60pcs / Tube         |
|              | Q3031W / Q3032W / Q3033W          | W       | Wide lead bend (0.4 inch spacing)                     | 60pcs / Tube         |
|              | Q3031WV / Q3032WV / Q3033WV       | W       | Wide lead bend (0.4 inch spacing) + VDE marking       | 60pcs / Tube         |
|              | Q3031STA / Q3032STA / Q3033STA    | S       | SMD lead form with tape and reel option               | 1000pcs / reel       |
|              | Q3031STAV / Q3032STAV / Q3033STAV | S       | SMD lead form with tape and reel option + VDE marking | 1000pcs / reel       |
| Q304X series | Q3041 / Q3042 / Q3043             | None    | Standard 6pin DIP                                     | 60pcs / Tube         |
|              | Q3041V / Q3042V / Q3043V          | None    | Standard 6 pin Dip + With VDE marking                 | 60pcs / Tube         |
|              | Q3041W / Q3042W / Q3043W          | W       | Wide lead bend (0.4 inch spacing)                     | 60pcs / Tube         |
|              | Q3041WV / Q3042WV / Q3043WV       | W       | Wide lead bend (0.4 inch spacing) + VDE marking       | 60pcs / Tube         |
|              | Q3041STA / Q3042STA / Q3043STA    | S       | SMD lead form with tape and reel option               | 1000pcs / reel       |
|              | Q3041STAV / Q3042STAV / Q3043STAV | S       | SMD lead form with tape and reel option + VDE marking | 1000pcs / reel       |
| Q306X series | Q3061 / Q3062 / Q3063             | None    | Standard 6pin DIP                                     | 60pcs / Tube         |
|              | Q3061V / Q3062V / Q3063V          | None    | Standard 6 pin Dip + With VDE marking                 | 60pcs / Tube         |
|              | Q3061W / Q3062W / Q3063W          | W       | Wide lead bend (0.4 inch spacing)                     | 60pcs / Tube         |
|              | Q3061WV / Q3062WV / Q3063WV       | W       | Wide lead bend (0.4 inch spacing) + VDE marking       | 60pcs / Tube         |
|              | Q3061STA / Q3062STA / Q3063STA    | S       | SMD lead form with tape and reel option               | 1000pcs / reel       |
|              | Q3061STAV / Q3062STAV / Q3063STAV | S       | SMD lead form with tape and reel option + VDE marking | 1000pcs / reel       |

|              |                                      |      |  |                |
|--------------|--------------------------------------|------|--|----------------|
| Q308X series | Q3081 / Q3082 / Q3083                | None | Standard 6pin DIP  | 60pcs / Tube   |
|              | Q3081V / Q3082V /<br>Q3083V          | None | Standard 6 pin Dip + With<br>VDE marking                 | 60pcs / Tube   |
|              | Q3081W / Q3082W /<br>Q3083W          | W    | Wide lead bend (0.4 inch<br>spacing)                     | 60pcs / Tube   |
|              | Q3081WV / Q3082WV /<br>Q3083WV       | W    | Wide lead bend (0.4 inch<br>spacing) + VDE marking       | 60pcs / Tube   |
|              | Q3081STA / Q3082STA /<br>Q3083STA    | S    | SMD lead form with tape and<br>reel option               | 1000pcs / reel |
|              | Q3081STAV / Q3082STAV<br>/ Q3083STAV | S    | SMD lead form with tape and<br>reel option + VDE marking | 1000pcs / reel |

## Revision History:

| Description:   | Revision # | Revision Date |
|--|------------|---------------|
| Initial of Q303X/Q304X/Q306X/Q308X series                            | 1.0        | 4/22/2010     |
| Feature, certification & compliance and ordering information updates | 1.1        | 02/01/2011    |
|  |            |               |
|  |            |               |
|  |            |               |

## Disclaimer

QT-BRIGHTTEK reserves the right to make changes without further notice to any products herein to improve reliability, function or design. QT-BRIGHTTEK does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

## Life Support Policy

QT-BRIGHTTEK's products are not authorized for use as critical components in life support devices or systems without the express written approval of QT-BRIGHTTEK. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.