

QT-Brightek Chip LED Series

0402 SMD Green LED

Part No.: QBLP595-2IG-2897

2897: High Brightness Version

Table of Contents:

Introduction 3

Electrical / Optical Characteristic (Ta=25 °C) 4

Absolute Maximum Rating 4

Characteristic Curves..... 5

Solder Profile & Footprint..... 6

Packing 7

Labeling 8

Ordering Information 8

Revision History 9

Disclaimer 9

Introduction

Feature:

- Water clear lens
- Package in tape and reel
- Color: green
- Compact 0402 package
- InGaN technology
- Viewing angle: 140° typ.
- Height profile: 0.5mm

Application:


- Status indication
- Back lighting application

Certification & Compliance:

- ISO9001
- RoHS Compliant



Dimension:



Units: mm / tolerance = +/-0.1mm

Electrical / Optical Characteristic (Ta=25 °C)

Product	Color	I _F (mA)	V _F (V)		λ _D (nm)			λ _P (nm)	I _V (mcd)	
			Typ.	Max.	Min.	Typ.	Max.	Typ.	Min.	Typ.
QBLP595-2IG-2897	Green	20	3.1	3.7	520	525	530	515	450	850

Absolute Maximum Rating

Chip Material	P _d (mW)	I _F (mA)	I _{FP} (mA)*	V _R (V)	T _{OP} (°C)	T _{ST} (°C)	T _{SO L} (°C)**
InGaN	93	30	100	5	-40 ~ +80	-40 ~ +85	260

*Duty 1/10 @ 1KHz

**IR Reflow for no more than 10 sec @ 260 °C

Forward Voltage V_F @ I_F=20mA

Bin	Min.	Max.	Unit
f	2.8	3.1	V
g	3.1	3.4	
h	3.4	3.7	




Luminous Intensity I_V @ I_F=20mA

Bin	Min.	Max.	Unit
1B	450	565	mcd
2B	565	706	
3B	706	883	
4B	883	1104	
5B	1104	1380	

Dominant Wavelength λ_D @ I_F=20mA


Bin	Min.	Max.	Unit
U	520	522.5	nm
V	522.5	525	
W	525	527.5	
X	527.5	530	

Characteristic Curves




Solder Profile & Footprint

-The recommended reflow soldering profile is as follows (temperatures indicated are as measured on the surface of the LED resin):




Recommended Pad Layout



Units: mm


Packing

Reel Dimension:




(Unit: mm)

Tape Dimension:





(Unit: mm)

Arrangement of Tape:



Packaging Specifications:





Made in China

Ordering Information

Orderable Part #	Spec Range	Quantity per reel
QBLP595-2IG-2897	Iv=850mcd typ. @ 20mA, λ_D =520nm to 530nm	5,000 units

Product: QBLP595-2IG-2897	Date: April 11, 2025	Page 8 of 9
	Version# 1.0	



Revision History

Description:	Revision #	Revision Date
New Release of QBLP595-2IG5-2897	V1.0	04/11/2025



Disclaimer

QT-BRIGHTEK reserves the right to make changes without further notice to any products herein to improve reliability, function or design. QT-BRIGHTEK does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

Life Support Policy

QT-BRIGHTEK’s products are not authorized for use as critical components in life support devices or systems without the express written approval of QT-BRIGHTEK. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.