

# **QT-Brightek Chip LED Series**

## **0402 SMD Green LED**

**Part No.: QBLP595-2IG5-2897**

**5: 5mA**

Table of Contents:

Introduction ..... 3

Electrical / Optical Characteristic (Ta=25 °C) ..... 4

Absolute Maximum Rating ..... 4

Characteristic Curves..... 5

Solder Profile & Footprint..... 6

Packing ..... 7

Labeling ..... 8

Ordering Information ..... 8

Revision History ..... 9

Disclaimer ..... 9

## Introduction

### Feature:

- Water clear lens
- Package in tape and reel
- Color: green
- Compact 0402 package
- InGaN technology
- Viewing angle: 140° typ.
- Height profile: 0.5mm

### Application:


- Status indication
- Back lighting application

### Certification & Compliance:

- ISO9001
- RoHS Compliant



### Dimension:



Units: mm / tolerance = +/-0.1mm

## Electrical / Optical Characteristic (Ta=25 °C)

| Product           | Color | I <sub>F</sub> (mA) | V <sub>F</sub> (V) |      | λ <sub>D</sub> (nm) |      |      | λ <sub>P</sub> (nm) | I <sub>V</sub> (mcd) |      |
|-------------------|-------|---------------------|--------------------|------|---------------------|------|------|---------------------|----------------------|------|
|                   |       |                     | Typ.               | Max. | Min.                | Typ. | Max. | Typ.                | Min.                 | Typ. |
| QBLP595-2IG5-2897 | Green | 5                   | 2.7                | 3.1  | 525                 | 530  | 535  | 520                 | 190                  | 370  |

## Absolute Maximum Rating

| Chip Material | P <sub>d</sub> (mW) | I <sub>F</sub> (mA) | I <sub>FP</sub> (mA)* | V <sub>R</sub> (V) | T <sub>OP</sub> (°C) | T <sub>ST</sub> (°C) | T <sub>SOL</sub> (°C)** |
|---------------|---------------------|---------------------|-----------------------|--------------------|----------------------|----------------------|-------------------------|
| InGaN         | 93                  | 30                  | 100                   | 5                  | -40 ~ +80            | -40 ~ +85            | 260                     |

\*Duty 1/10 @ 1KHz

\*\*IR Reflow for no more than 10 sec @ 260 °C

## Forward Voltage V<sub>F</sub> @ I<sub>F</sub>=5mA

| Bin | Min. | Max. | Unit |
|-----|------|------|------|
| e   | 2.5  | 2.8  | V    |
| f   | 2.8  | 3.1  |      |




## Luminous Intensity I<sub>V</sub> @ I<sub>F</sub>=5mA

| Bin | Min. | Max. | Unit |
|-----|------|------|------|
| 2L  | 190  | 238  | mcd  |
| 2M  | 238  | 297  |      |
| 2N  | 297  | 371  |      |
| 2O  | 371  | 464  |      |
| 2P  | 464  | 580  |      |

## Dominant Wavelength λ<sub>D</sub> @ I<sub>F</sub>=5mA


| Bin | Min.  | Max.  | Unit |
|-----|-------|-------|------|
| W   | 525   | 527.5 | nm   |
| X   | 527.5 | 530   |      |
| Y   | 530   | 532.5 |      |
| Z   | 532.5 | 535   |      |

## Characteristic Curves




Solder Profile & Footprint

-The recommended reflow soldering profile is as follows (temperatures indicated are as measured on the surface of the LED resin):




Recommended Pad Layout



Units: mm


Packing

Reel Dimension:




(Unit: mm)

Tape Dimension:




(Unit: mm)

Arrangement of Tape:



Packaging Specifications:







---

## Revision History

| Description:                     | Revision # | Revision Date |
|----------------------------------|------------|---------------|
| New Release of QBLP595-2IG5-2897 | V1.0       | 04/11/2025    |
|                                  |            |               |
|                                  |            |               |
|                                  |            |               |
|                                  |            |               |
|                                  |            |               |
|                                  |            |               |

## Disclaimer

QT-BRIGHTEK reserves the right to make changes without further notice to any products herein to improve reliability, function or design. QT-BRIGHTEK does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

## Life Support Policy

QT-BRIGHTEK's products are not authorized for use as critical components in life support devices or systems without the express written approval of QT-BRIGHTEK. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

|                            |                      |             |
|----------------------------|----------------------|-------------|
| Product: QBLP595-2IG5-2897 | Date: April 11, 2025 | Page 9 of 9 |
|                            | Version# 1.0         |             |