

QT-Brightek Chip LED Series

0603 SMD Chip LED

Part No.: QBLP601L-2IW5-2897

L: Low Profile

5: 5mA

2897: High Brightness Version

Table of Contents:

Introduction 3

Electrical / Optical Characteristic (Ta=25 °C) 4

Absolute Maximum Rating 4

Chromaticity Coordinate Chart..... 5

Characteristic Curves..... 6

Solder Profile & Footprint..... 7

Packing 8

Labeling 9

Ordering Information 9


Revision History 10

Disclaimer 10

Introduction

Feature:

- Yellow diffused lens
- Package in tape and reel
- Compact 0603 package
- Viewing angle: 140° typ.
- Height profile: 0.4mm



Application:


- Status indication
- Back lighting application

Certification & Compliance:

- ISO9001
- RoHS Compliant



Dimension:



Units: mm / tolerance = +/-0.1mm

Electrical / Optical Characteristic (Ta=25 °C)

Product	Color	I _F (mA)	V _F (V)		CIE Coordinate	I _V (mcd)	
			Typ.	Max.	Typ.	Min.	Typ.
QBLP601L-2IW5-2897	White	5	2.7	3.4	X=0.29 Y=0.282	250	475

Absolute Maximum Rating

Chip Material	P _d (mW)	I _F (mA)	I _{FP} (mA)*	V _R (V)	T _{OP} (°C)	T _{ST} (°C)	T _{SOL} (°C)**
InGaN	102	30	100	5	-40 ~ +80	-40 ~ +85	260

*Duty 1/10 @ 1KHz

**IR Reflow for no more than 10 sec @ 260 °C


Forward Voltage V_F @ I_F=5mA

Bin	Min.	Max.	Unit
e	2.5	2.8	V
f	2.8	3.1	
g	3.1	3.4	

Luminous Intensity I_V @ I_F=5mA

Bin	Min.	Max.	Unit
L	250	313	mcd
M	313	390	
N	390	488	
O	488	610	
P	610	762	


Chromaticity Coordinate Chart




C1	X	0.25	0.25	0.27	0.27
	Y	0.205	0.25	0.2775	0.2325
C2	X	0.27	0.27	0.29	0.29
	Y	0.2325	0.2775	0.305	0.26
D1	X	0.29	0.29	0.31	0.31
	Y	0.26	0.305	0.3325	0.2875
D2	X	0.31	0.31	0.33	0.33
	Y	0.2875	0.3325	0.36	0.315

Characteristic Curves


Forward Current vs. Forward Voltage



Relative Intensity vs. Wavelength




Directive Characteristics




Solder Profile & Footprint

-The recommended reflow soldering profile is as follows (temperatures indicated are as measured on the surface of the LED resin):




Recommended Pad Layout



Units: mm


Packing

Reel Dimension:




(Unit: mm)

Tape Dimension:




(Unit: mm)

Arrangement of Tape:



Packaging Specifications:





Revision History

Description:	Revision #	Revision Date
New Release of QBLP595-2IW5-2897	V1.0	05/08/2025

Disclaimer

QT-BRIGHTEK reserves the right to make changes without further notice to any products herein to improve reliability, function or design. QT-BRIGHTEK does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

Life Support Policy

QT-BRIGHTEK's products are not authorized for use as critical components in life support devices or systems without the express written approval of QT-BRIGHTEK. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Product: QBLP601L-2IW5-2897	Date: May 15, 2025	Page 10 of 10
	Version# 1.0	