

QT-Brightek Chip LED Series

SMD 1205 LED

Part No.: QBLP655R-O-2897

**655R: Reverse Mount
2897: High Bright**

Product: QBLP655R-O-2897	Date: February 10, 2026	Page 1 of 9
	Version# 1.0	

Table of Contents:

Introduction

Electrical / Optical Characteristic (Ta=25 °C)

Absolute Maximum Rating

Characteristic Curves.....

Solder Profile & Footprint.....

Packing

Labeling

Ordering Information

Revision History

Disclaimer

3

4

4

5

6

7

8

8


9

9

Introduction

Feature:

- Clear lens
- Package in tape and reel
- High bright orange
- Viewing angle: 140 degrees typ.
- Reverse mount
- Height profile: 1.1mm



Application:


- Status indication
- Back lighting application

Certification & Compliance:

- ISO9001
- RoHS Compliant



Dimension:



Units: mm / tolerance = +/-0.1mm

Electrical / Optical Characteristic (Ta=25 °C)

Product	Color	I _F (mA)	V _F (V)		λ _D (nm)			λ _p (nm)	I _v (mcd)	
			Typ.	Max.	Min.	Typ.	Max.	Typ.	Min.	Typ.
QBLP655R-O-2897	Orange	20	2.0	2.5	600	605	610	610	215	410

Absolute Maximum Rating

Chip Material	P _d (mW)	I _F (mA)	I _{FP} (mA)*	V _R (V)	T _{OP} (°C)	T _{ST} (°C)	T _{SOL} (°C)**
AllnGaP	75	30	100	5	-40 ~ +80	-40 ~ +85	260

*Duty 1/10 @ 1kHz

**IR Reflow for no more than 10 sec @ 260 °C

Forward Voltage V_F @ I_F=20mA

Bin	Min.	Max.	Unit
□	1.7	2.5	V

Luminous Intensity I_v @ I_F=20mA


Bin	Min.	Max.	Unit
2M	215	269	mcd
2N	269	345	
2O	345	431	
2P	431	539	
2Q	539	680	

Dominant Wavelength λ_D @ I_F=20mA


Bin	Min.	Max.	Unit
p	600	605	nm
q	605	610	

Characteristic Curves


Relative Intensity vs. Wavelength



Forward Current vs. Forward Voltage




Directive Characteristics




Solder Profile & Footprint

-The recommended reflow soldering profile is as follows (temperatures indicated are as measured on the surface of the LED resin):




Recommended Pad Layout



Units: mm


Packing

Reel Dimension:




Unit: mm

Tape Dimension:




Unit: mm

Arrangement of Tape:



Packaging Specifications:



Labeling



QT-Brightek





Part No:

Customer P/N:

Item:

Q'ty:

Vf:

Iv:

WI:

Date:

Made in China

Ordering Information

Orderable Part #	Spec Range	Quantity per reel
QBLP655R-O-2897	Iv=410mcd typ. @ If=20mA / λD=600-610nm	3,000 units

Revision History

Description:	Revision #	Revision Date
New Release of QBLP655R-O-2897	V1.0	2/10/2026

Disclaimer

QT-BRIGHTEK reserves the right to make changes without further notice to any products herein to improve reliability, function or design. QT-BRIGHTEK does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

Life Support Policy

QT-BRIGHTEK's products are not authorized for use as critical components in life support devices or systems without the express written approval of QT-BRIGHTEK. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.